

| | |
|-----|---|
| 15. | <h2 style="margin: 0;">HIWIN Customer Requirements(LA)</h2> |
|-----|---|

| | | | |
|----------------------------|--|-----------------|--|
| Customer: | | Contact person: | |
| | | Tel: | |
| | | Fax: | |
| Voltage VDC | | Notes: | |
| No-Load current | | | |
| Max. current | | | |
| Max. thrust force | | | |
| Max. pulling force | | | |
| Max. holding force | | | |
| Stroke | | | |
| Install length | | | |
| Speed (mm/s) | | | |
| Load (N) | | | |
| Duty cycle 10% | | | |
| Operation temp | | | |
| IP Codes | | | |
| Outdoor use | <input type="checkbox"/> YES <input type="checkbox"/> NO | | |
| Direction | <input type="checkbox"/> H <input type="checkbox"/> V | | |
| Axial load | <input type="checkbox"/> YES <input type="checkbox"/> NO | | |
| With L/S | <input type="checkbox"/> YES <input type="checkbox"/> NO | | |
| With control | <input type="checkbox"/> YES <input type="checkbox"/> NO | | |
| Over current | <input type="checkbox"/> YES <input type="checkbox"/> NO | | |
| With customer's L/S | | | |
| Position capability | | | |
| Special design | | | |
| Expected price | | | |
| Quantity | | | |
| Recommended specification: | | | |
| | | | |
| Engineer: | | | |