A10JSGA1 | Released by HIWIN design group.





D-D VIEW



F0.4X0.2DIN509

X DETAIL

1. MAX AXIAL LOAD: _____kgf
2. MAX BALLSCREW ROTATIONAL SPEED: _____rpm
   DN VALUE: _____
   ACCELERATION=____m/sec²
3. MAX FEED RATE: _____m/min

PRELOAD(kgf)	207
R.D	29.324
S.F (kgf)	0.65~1.92
DRAG TORQUE(kgf-cm)	1.88~5.64
LUBRICATION	——
DIRECTION OF TURN	R.H
PC DIA.	32.6
BALL DIA.	3.175
BACKLASH	0
CIRCUIT	2.5*2
LEAD ANGLE	2.84°
DYNAMIC (kgf)	1886
STATIC (kgf)	5666
LEAD	5.08

SPEC: R32-5.08B2-FSV-865.38-1320.8-0.012

MAT.	SH: 50CrMo4	DATE	11.29'01
	NT: SNCM220	DWG	張簡睿
THREAD BALL TRACK HRC 58 ~ 62		APPD	
		PROCESS NO.	G E
CUSTR	HIWIN STD.		
DWG.NO.	A10JSGA1		

UNCHAMFERED USE ☐R0.5 ■R1 ☐R
ROUGH 25▽ | F/C 6.3▽ | F/N 6.3▽ | M/C 0.4▽ | GRD ▽▽ | SCALE 1:X
UNTOL DIMN mm

UP TO	6	30	120	300	600	1200	OVER 2400
±0.1	±0.2	±0.3	±0.4	±0.5	±0.8	±1.0	±1.5

THREAD LENGTH

T:-0.026 ø.OOD: 0.012
E: 0.021 e: 0.017

*BREAK SHARP EDGE UNLESS OTHER SPECIFIED. CUSTOMER DRAWING NO.
*未盡倒角者以R0.5MAX
THREAD END ALIGNS ABOVE LENGTH OUT OF HARDNESS TOLERANCE
MC TYPE
NAL TYPE

DATE	MODIFICATION	APPROVED

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

HIWIN BALLSCREWS